

## EJOT® self-drilling screw JT2-12-5.5



### Application range

- > Fastening profiled steel sheets to 4–12 mm steel substructure

### Properties

- > Case-hardened steel
- > High-grade coating to improve the corrosion protection
- > Steel sealing washer, zinc-plated
- > Pre-assembled sealing washer

### Applications



### Technical data

AF8	5.5	1/min max. 1500
1.0 + 12.0	2.0 + 10.0	V16

### Cross references

Socket wrench insert  
Cordless screwdriver ASCS 6.3

### Certifications



### Online shop



Order description	Length [mm]	Diameter [mm]	Clamp thickness [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
<b>Sealing washer V16, Ø 16 mm</b>							
JT2-12-5.5x35-V16	35	5.5	0 - 10	500		3 804 521 997	4061245014944
JT2-12-5.5x35-V16 VE100	35	5.5	0 - 10	100		6 804 521 997	4061245014562
JT2-12-5.5x50-V16	50	5.5	0 - 25	250		3 807 121 997	4061245014937
JT2-12-5.5x50-V16 VE100	50	5.5	0 - 25	100		6 807 121 997	4061245014548
JT2-12-5.5x65-V16	65	5.5	6 - 40	250		3 807 521 997	4061245014920
JT2-12-5.5x65-V16 VE100	65	5.5	6 - 40	100		6 807 521 997	4061245014531